High Efficiency EHA105 ElectroComp Agrobacterium

Description

Intact Genomics EHA105 ElectroComp Agrobacterium cells are optimized for the highest transformation efficiencies which is ideal for applications requiring high transformation efficiencies, such as with cDNA or gDNA library construction. The EHA105 strain is useful for transgenic operations of rice, tobacco and other plants. EHA105 contains a rifampicin resistance gene (rif). EHA105 strain also contains an amber basic Ti plasmid pEHA105 (pTiBo542DT-DNA) without self-transport function, which contains the vir gene.

Specifications

Competent cell type: Electrocompetent Species: A. tumefaciens

Strain: EHA105 Format: Tubes

Transformation efficiency: $\geq 1 \times 10^7 \text{ cfu/µg}$

pCAMBIA1391z DNA

Blue/white screening: No Shipping condition: Dry ice

Genotype

C58 (rif r) Ti pEHA105 (pTiBo542DT-DNA) Succinamopine

Reagents Needed for One Reaction

EHA105 ElectroComp Agrobacterium: 25 μl DNA (pCAMBIA1391z, 100 pg/μl): 1 μl Recovery medium: 1 ml

Storage

EHA105 ElectroComp Agrobacterium: -80 °C pCAMBIA1391z control DNA: -20 °C Recovery medium: 4 °C

Quality Control

Transformation efficiency is tested by using the pCAM-BIA1391z control DNA supplied with the kit and using the protocol in this manual. Transformation efficiency should be $\geq 1 \times 10^7 \, \text{CFU/\mug}$ pCAMBIA1391z DNA. Untransformed cells are tested for appropriate antibiotic sensitivity.

General Guidelines

Follow these guidelines when using EHA105 Electro-Comp Agrobacterium:

- Handle competent cells gently as they are highly sensitive to changes in temperature or mechanical lysis caused by pipetting.
- Thaw competent cells on ice, and transform cells immediately following thawing. After adding DNA, mix by tapping the tube gently. Do not mix cells by pipetting or vortexing.

Note: A high-voltage electroporation apparatus such as Bio-Rad Gene Pulser II #165-2105, capable of generating field strengths of 16 kV/cm is required.

Calculation of Transformation Efficiency

Transformation Efficiency (TE) is defined as the number of colony forming units (cfu) produced by transforming 1µg of plasmid into a given volume of competent cells.

TE = Colonies/µg/Plated

Transform 1 μ I of (500 pg/ μ I) pCAMBIA1391z control plasmid into 25 μ I of cells, add 974 μ I of Recovery Medium. Recover for 3 hours and plate 100 μ I. Count the colonies on the plate in two days. If you count 500 colonies, the TE is calculated as follows:

Colonies = 500 µg of DNA = 0.0005 Dilution = 100/1000 = 0.1 TE = 500/.0005/.1 = 1x10⁷

Transformation Protocol

Use this procedure to transform EHA105 ElectroComp Agrobacterium. Do not use these cells for chemically transformation.

- Place sterile cuvettes and microcentrifuge tubes on ice.
- 2) Remove competent cells from the -80 °C freezer and thaw completely on wet ice (10-15 minutes).

- Aliquot 1 μI (10pg -1 μg) of DNA to the chilled microcentrifuge tubes on ice.
- 4) When the cells are thawed, add 25 μl of cells to each DNA tube on ice and mix gently by tapping 4-5 times. For the pCAMBIA1391z control, add 1 μl of (500 pg/ μl) DNA to the 25 μl of cells on ice. Mix well by tapping. Do not pipette up and down or vortex to mix, this can harm cells and decrease transformation efficiency.
- 5) Pipette 26 µl of the cell/DNA mixture into a chilled electroporation cuvette without introducing bubbles. Quickly flick the cuvette downward with your wrist to deposit the cells across the bottom of the well and then electroporate.
- 6) Immediately add 976 µI of Recovery Medium or any other medium of choice to the cuvette, pipette up and down three times to re-suspend the cells. Transfer the cells and Recovery Medium to an Eppendorf tube. .
- Incubate tubes at 30 °C for 3 hours at 200 RPM.
- 8) Dilute the cells as appropriate then spread 20-200 μl cells onto a pre-warmed selective plate. For the pCAMBIA1391z control, you may plate 50 μl of diluted transformants onto a YT plate containing 15 μg/ml rifampicin and 50 μg/ml kanamycin. Use sterilized spreader or autoclaved ColiRoller™ plating beads to spread evenly.
- Incubate the plates for 2 3 days at 30 °C.

Electroportation settings

Mode Exponential protocol

Voltage (V) 1,800 V
Capacitance 25 uFD
Resistance 200 Ohms
Cuvette 1 mm